

# ***AINTEGRITY EDGE***

## Quality Assurance Programme

### **PAINTER/GRANO APPLICATOR:**

---

SITE ADDRESS:

---

### **OHS**

- New contractors to complete TAC before commencement of work ([www.integritynewhomes.com.au/tradecontractorlogin](http://www.integritynewhomes.com.au/tradecontractorlogin) username: subcontractor; password: integrity)
- Ensure you have a SWMS, a MSDS (if applicable) and general induction numbers.
- Ensure that you carry an Australian Standard compliant and current, first aid kit in your vehicle at all times when on an Integrity site – this kit should be construction site and employee number appropriate.

### **GENERAL**

- Ensure manufacturer sealer is used and all products are part of the manufacturer's system.
- Meet with the client at the commencement of job and provide a site sample of internal and external finishes. Have the client sign off over page.
- A *Dulux/Integrity New Homes Project Activity Card* must be presented at the Dulux Trade Outlet for all paint purchases for INH jobs.

To setup a Dulux account and a *Dulux Project Activity Card* please contact:

STATE	CONTACT NAME	PHONE
NSW & ACT	Murray Power	0417 673 927
QLD	Amanda Rackham	0428 172 782
WA	Carl McKeon	0401 138 052
SA	Esther McConnell	0427 876 289
VIC	Michelle Hedge	0401 990 696

Date:

Unless specified otherwise in the Addendum A of the Building Contract the following paint system is to be used.

INTERNAL		
AREA	COATS	PRODUCT
Walls, Plasterboard	1	Berger Gold Label Acrylic Sealer undercoat
	2	Dulux Wash&Wear Low Sheen or Int/Ext Matt
Walls, Whiteset	1	Berger GL Plasterwall Sealer OB
	2	Dulux Professional Int Matt
Ceilings, Plasterboard	2	Hadrian Contractor 2000 Flat <i>(areas subject to glancing light add 1 coat Berger Gold Label UC)</i>
Internal Wood, Painted (skirting, architraves)	1	Dulux Professional Total Prep
	2	Dulux Aquanamel High Gloss or Dulux Professional High Gloss Enamel
Internal Wood, Clear (skirting, architraves)	3	Intergrain Ultraclear Satin Interior
Internal Wood, Stained (skirting, architraves)	2	Intergrain Natural Stain (ref colour schedule for colour)
Doors, Internal	1	Dulux Professional Total Prep or Dulux Precision Max Adhesion Primer
	2	Dulux Aquanamel High Gloss or Dulux Professional High Gloss Enamel
Stairs, Stained Non slip additive must be added to the middle coat and applied to stair treads only	3	Cabots CFP Satin/Gloss or Intergrain Ultraclear Satin Interior <i>(middle coat requires minimum 5% Intergrain Ultragrip to be applied to treads)</i>
EXTERNAL		
AREA	COATS	PRODUCT
Doors, External	1	Dulux Professional Total Prep
	2	Dulux Aquanamel High Gloss or Dulux Professional High Gloss Enamel
Eaves, Fibre cement	2	Dulux Professional Exterior Low Sheen
Porch/Afresco, Fibre cement	2	Dulux Professional Exterior Low Sheen
Timber Decking	1	Intergrain Reviva Wood Cleaner
	2	Intergrain Ultradeck <i>(generous coats using applicator pad)</i>
Wood, Pre Primed	2	Dulux Professional Exterior Low Sheen <i>(test adhesion of primer before coating)</i>
Wood, Unprimed	2	Dulux Weathershield Low Sheen
Block/Brick, Rendered	2	Dulux AcraTex Sedona
Downpipes, PVC	2	Dulux Professional Exterior Low Sheen

- Ensure all plaster residue is removed from all surfaces to be painted.
- Minimum drying times stated on the cans of paint being used must be strictly adhered to.
- When using a spray application at least the first sealer coat must be back rolled.
- Paint top, bottom and sides of external, internal, cavity slider and wet area doors with at least one thick coat.**
- Check whether front doors are stained or painted.
- Any visible faulty plastering work after first coat must be attended to by plasterer or painter prior to second coat.
- All architraves and skirting to be filled and sanded flush, no divets accepted.
- Polyurethane joint sealant (like Sikaflex) to be used externally around all windows where lightweight cladding is used.
- Polyurethane joint sealant (like Sikaflex) to be used internally where kitchen bulkheads meet the cornice, walls and/or ceiling.
- Drop sheets must be used, any cleaning due to overspray will be back charged to the painter. (Especially in the tile areas and garage).
- Back roll all ceilings and all spray painted applications.
- Use 11 nap Dulux Professional synthetic roller sleeve on interior wall and ceiling finishes.
- 'Light Checks' to be done on all internal surfaces.
- Touch up paint to be left in neat condition with touch up kit.
- All touch up tags to be picked up and disposed of.
- Paint wash up and disposal must be done using a method approved by local council, such as EnviroWash unit or equivalent.
- Complete and sign Integrity Edge and submit with invoice at end of job.

**CLIENT CONFIRMATION**

I confirm that the site samples provide by the applicator/painter are approved.

Client Signature: \_\_\_\_\_ Date: \_\_\_\_\_

Painters Signature: \_\_\_\_\_ Invoice Number: \_\_\_\_\_