

INTEGRITY EDGE

Quality Assurance Programme

WATERPROOFER:

SITE ADDRESS:

OHS

- New contractors to complete TAC before commencement of work (www.integritynewhomes.com.au/tradecontractorlogin username: subcontractor; password: integrity)
- Provide project manager with SWMS (where required) and general induction numbers.
- Record the products used in the OHS Hazardous Substance Register and leave the MSDS with the Risk Register.
- Ensure that you carry an Australian Standard Compliant, First Aid Kit in your vehicle at all times when on an Integrity site – this kit should be construction site & employee number appropriate.

GENERAL

- All areas to be cleaned thoroughly mechanically and chemically (ie clean off all dags and ensure square corners) before application of waterproofing products,
- Shower hobs are to 65 x 50 Hebel unless otherwise specified on the plans or contract addendum.
- All shower walls to be waterproofed.
- Flanges are to be fitted to all shower plumbing penetrations to AS 3740-2004.
- All waterproofing to comply with AS 3740 – 2010 and BCA Volume 2 Table 3.8.1.1
- The tile angle to bathroom doors is to be 45mm unless noted otherwise on the engineering/architectural plans. Ensure tile angle is installed level – pack/caulk if required.

Date: _____

FINISHING

- Provide a fact sheet for the tiler which nominates the glues which are compatible with the waterproofing product used. Leave this in a prominent location onsite.**
- Call certifying authority and book inspection.
- Clean out job and sweep before leaving.
- Ensure that when you leave the house is secure. If not, you will be liable for theft and any damage that may be caused.
- Provide certificate certifying that the waterproofing has been completed in accordance with the BCA and Australian Standard.
- Complete and sign Integrity Edge and submit with invoice at end of job.

Signature: _____ Date: _____

Print Name: _____ Invoice No: _____